Page 1 of 1 Hallco Industries, Inc.



## THE ORIGINAL LIME FLOOR™ SYSTEM.



## DRIVE DESCRIPTION:

Every HALLCO drive unit is custom designed and built to match the individual customer's application and load weight. The 4000 Series, our most popular unit, is often called the "work horse" with thousands of trouble-free units in service. The 4000 Series is widely used for refuse hauling and is well matched to trailers hauling legal trailer payloads. Depending on the deck configuration this drive unit can handle anything from woody biomass and recyclables to C&D debris and

Features	Specifications
Load Rating	35 Ton
	1
# Cylinders	6
Stroke	10"
Piston Diameter	3"
Rod Diameter	1.5"
Shaft Coating	Double Chrome
Effective Piston Area	12.37 in <sup>2</sup>
Rated Pressure	3000 PSI
Rated Flow	30 GPM
Theoretical Convey Speed (max flow)	6.43 ft/min
Mount Style	Under Mount
Convey Direction Options	One-Way & Two-Way
Hydraulic Module (only) Weight	230 lb
Deck Compatibility	Standard
	Double Ridge
	Triple Ridge
	Topseal
	Tufdeck
	Leak Resistant
	HD Leak Resistant
:0000	Tufdeck Leak Resistant

Mini Drive

2000

3000

i-3000

4000

6000

i-6000



8000





HOME | ABOUT US | WHY CHOOSE LIVE FLOORS? | HOW IT WORKS | PRODUCTS | INDUSTRIES | DOCUMENTS | DEALER DIRECTORY | CONTACT US COPYRIGHT © 2012, HALLCO INDUSTRIES INC. ALL RIGHTS RESERVED | LEGAL EMPLOYEE LOGIN | CAREER OPPORTUNITIES

HALLCO LIVE FLOORS® TRADEMARK GUIDELINES (.PDF)